

you can
Canon

i-SENSYS
MF4370dn

Laser Mono
Multifunctional Printer

Compact, complete and
network-ready laser All-in-One

i-SENSYS MF4370dn

Small workgroups can share all the productive functions of this compact, network-ready communication centre. Print, fax, copy and scan – with fast, professional mono laser output – and benefit from energy efficiency and automatic double-sided printing.



22ppm
monochrome
printing

250-sheet
paper tray

Virtually zero
warm-up time

1200 x 600dpi
print resolution

9600 x 9600dpi
Colour scanning

Duplex
printing



WHAT'S IN THE BOX

Main unit, cartridge FX10, power cable, USB cable, telephone line cable, starter guide, manuals on CD, user software CD, warranty card.

KEY FEATURES

- Compact laser All-in-One: print, fax, copy and scan
- 22 ppm mono printing and copying
- No waiting with Quick First-Print technologies
- First Copy Out Time of 9 seconds or less
- Automatic double-sided printing
- Up to 1200 x 600 dpi print resolution
- Colour scanning: up to 9600 x 9600 dpi, save as PDF
- Super G3 fax with 256-page memory*
- 35-sheet Automatic Document feeder
- 250-sheet paper tray
- Energy saving – only 3 watts in sleep mode
- Maintenance-free All-in-One Cartridge for continuous high quality output
- Network ready with Remote User Interface (RUI)

* Based on ITU-T Standard Chart No. 1

DIMENSIONS (W x D x H)

390 mm x 442 mm x 455 mm

SUPPORTED OS

Windows 2000/ XP/ Server 2003/ Vista

Mac OS X version 10.2.8-10.5.x (Web distribution only)

Linux (Web distribution only & English print driver only)



PRINT




COPY



FAX



SCAN



- 1 Flatbed and ADF
- 2 250-sheet tray
- 3 Optional telephone handset
- 4 FX10 cartridge

Specifications

Machine type Available functions	Mono Laser All-in-One Print, Copy, Scan and Fax
PRINTER Print speed Printing method Print quality Print resolution Double sided printing Printer languages Print margins Toner saver mode	Up to 22 ppm (A4) Monochrome laser beam printing Up to 1200 x 600 dpi with Automatic Image Refinement 600 x 600 dpi Automatic UFR II-LT 6 mm-top and bottom, 5 mm-left and right Yes
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Double sided copying Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 22 cpm (A4) Approx. 9 seconds or less Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo 1-sided to 2-sided (Manual) Up to 99 copies 50-200% in 1% increments Yes Collate, 2 on 1
SCANNER Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 1200 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN, WIA 216 mm
FAX Modem speed Receive mode Fax resolution Fax memory Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing Other features	Super G3 33.6kbps (Up to 3 seconds/page ¹) Fax only, Fax/Tel Auto Switch, Answer Mode, Manual Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Up to 256 pages ¹ Max. 107 (including 7 one-touch dials) Max. 8 dials/ Max.50 destinations Max. 123 locations 5 mins Yes (Receive) Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)
MEDIA HANDLING Scanner type Paper input (Standard) Paper output Media types	Flatbed and Automatic Document Feeder (ADF) 250-sheets tray 1-sheet manual feed slot 35-sheets ADF 100-sheets Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope

Media sizes	Tray: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 x 127 mm; Length 216 x 356 mm. Manual feed slot: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 x 127 mm; Length 216 x 356 mm. ADF: A4, A5, Legal, Letter, Custom (W x L): Max 216 x 356 mm
Media weights	Min 105 x 148.5 mm Tray: 64 to 128 g/m ² Manual feed slot: 64 to 163 g/m ² ADF: 40 to 105 g/m ²
INTERFACE & SOFTWARE Interface type Operating System compatibility Software and printer management	USB 2.0 Hi-speed, 10BASE-T/100BASE-TX Windows 2000/ XP/ Server 2003/ Vista Mac OS X version 10.2.8-10.5.x ^{2 3} Linux ^{2 4} Omni Page SE, Presto! Page Manager, MF toolbox, Remote User Interface (RUI)
GENERAL FEATURES Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption Noise Levels	Max. 10,000 pages per month Approx. 12 seconds from power on 32 MB (shared) 16 characters x 2 lines backlit LCD 390 mm x 442 mm x 455 mm 390 mm x 813 mm x 588 mm Approx. 15.15 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. less than 650 W Active: Approx. less than 650 W Standby: Approx. less than 9 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 1.028 kWh/week Sound Pressure ⁵ Active: 63.5 dB(A) or less Standby: Inaudible
CONSUMABLES Cartridges	Cartridge FX10 (2,000 pages ⁶)
ACCESSORIES/ OPTIONS Items	Telephone 6 Kit Black

All specifications subject to change without notice

¹ Based on ITU-T Standard Chart No. 1

² Web distribution only

³ Network scanning is not supported

⁴ English print driver only

⁵ Declared noise emission in accordance with ISO 9296

⁶ Based on 5% coverage

